



2024 ASV RT135F

[Read More](#)

SKU:PRIMP472

Price:\$138000

Categories:[Skid Steer Loader](#)

Product Description

The RT-135 Forestry make impossible jobs seems ordinary. Comfortable and easy to operate, the MAX-Series premium operator experience is front and center to getting big forestry jobs done. OPERATIONS Loader Arms Radial Operating Weight12990 lbs Rated Operating Capacity @ 35%4150 lbs Rated Operating Capacity @ 50%5929 lbs Ground Pressure4.6 psi Engine Power132 hp Tipping Load11858 lbs Travel Speed, Maximum - 1st Speed6 mph Travel Speed, Maximum - 2nd Speed10 mph AUXILIARY HYDRAULIC Controls Intermittent via joystick button or continuous via console switch. High-flow is adjustable and loader/auxiliary sharing is adjustable via machine display Couplers Push-to-connect quick couplers mounted on loader arms. Pressure relief valve on coupler block Cooling System High efficiency side-by-side radiator and oil cooler Pump Capacity Low20 gpm Pump Capacity High50 gpm System Pressure Max Low3300 psi System Pressure Max High4060 psi ENGINE Type Diesel 4-cylinder, turbo charged Model Cummins QSF3.8 Cooling System Temperature-controlled, variable speed and operator time-selectable, hydraulically-driven, auto-reversing fan and coolant/anti-freeze-filled radiator Intake Air Cleaner Three-stage Emission Controls Meets all U.S. EPA Tier 4 final standards Standard Feature Auto Idle Engine Power132 hp Gross Power Rating132 hp Torque Peak360 ft-lb Track Width20 in Length of Track on the Ground71 in Ground Contact Area2840 in² Roller Wheel Diameter Front & rear wheels15 in Roller Wheel Diameter Middle Wheel10 in OPERATOR STATION Seat Adjustable air ride contour vinyl seat with built-in operator presence switch, lap bar and 2 in. (51 mm) wide seat belt, operator manual pouch Loader Control Right-hand electronic joystick controls loader lift, lower and tilt, plus intermittent control of auxiliary hydraulic. Loader speed is adjustable and selectable from ISO or H control pattern Drive Control : Left-hand electronic joystick controls machine speed and direction. Track speed is adjustable, includes a Creep Mode and is selectable from ISO or H control pattern Engine Speed Hand-operated throttle and foot throttle 7-Inch Color Machine Display Engine RPM, engine oil pressure, hydraulic oil high temperature, engine coolant temperature, battery voltage, hour meter, fuel level, trip meter, engine diagnostics, system monitoring, fault logging, integrated rear view camera, password protection with user profiles, job clock, maintenance schedules, Def level, Adjustable controls, Adjustable hydraulic flows, winch (optional) control. ROPS ISO 8082-Forestry FOPS ISO 8083-Forestry OPS ISO 8084-Forestry, BC WCB G603 - Window guards for forestry, BC WCB G604 - Light duty screen guards for off highway, BC WCB G608 - Heavy duty roof structure, ISO 6683 - Seat belt anchors, CAL OSHA 1596 - Seat belt, SAE J2292 - Shoulder restraint (when equipped with 3 point options), ISO 11839 - Forestry thrown object guard Illumination 2 - Adjustable forward-facing LED lights, 2 - Adjustable rear-facing LED lights, 1 - Interior light, 2 - LED side lights Convenience 12 V power port Standard Features Horn, backup alarm, cup holder, phone holder, behind seat storage, rear view mirror, lapbar, roof escape hatch, roof panel & rear cab windows. Adjustable joystick & arm rest positions, adjustable directional & air flow HVAC vents, radio with bluetooth & USB, frameless front door, attachment control kit, wiper/washer, easy-off door